

VINIPROPRE

The high flow rate allows rinsing of filters and circuits with hot water continuously at 52° C.

The small flow allows disinfection of bottling lines from 90° to 97° C.

TECHNICAL DESCRIPTION

Electrical motor 5,5 HP	1
Pump High Pressure 35 bar	1
Fixed stainless steel frame	1
Horizontal stainless steel heating element	1
Stainless steel coil	1
Electrical fuel burner (up to 209 kW)	1
Stainless steel fuel tank according to model	1
Double thermostat according to model	1
Electrical control box on / off	1
Power cable	5 m
Time meter	1
Hose HP ND13 stainless steel fittings	2 m
Total stop re-engagement on Control box	1
1/2" stainless steel hydraulic fittings	✓



Autonomous
installation on truck





VINIPROPRE








The solution to clean and disinfect your wine bottling line

The high flow rate allows rinsing of filters and circuits with hot water continuously at 52° C.
The small flow allows disinfection of bottling lines from 90° to 97° C.

Code	Burner model	Pump Pressure	Pump Flow rate	Power motor	Electrical power	Flow control sensor	Heating serpentine	Performance
6.VI211001	Pro	35 Bar	15/30 L/min	5.5 HP	400 V - 50 Hz	With	short	Sterilization 13,2 L at 91° C and Rinsing 28,2 L at 50,1° C
6.VI211002	Evo	35 Bar	21/42 L/min	5.5 HP	400 V - 50 Hz	With	short	Sterilization 18,8 L at 94° C and Rinsing 40 L at 54° C
6.VI211003	Pro	35 Bar	17/34 L/min	5.5 HP	400 V - 50 Hz	With	long	Sterilization 15,4 L at 94° C and Rinsing 32,2 L at 57° C
6.VI211004	Evo	35 Bar	21/42 L/min	5.5 HP	400 V - 50 Hz	With	long	Sterilization 20,4 L at 93° C and Rinsing 42 L at 56° C

Dimensions (without foot nor wheel)

	PRO Boiler model	EVO Boiler model	Electrical control box
Length	1138 mm (44,8 inch)	1350 mm (53,15 inch)	400 x 300 mm (15,75 x 11,81 inch) Can be positioned at your convenience
Width	450 mm (17,72 inch)	500 mm (19,69 inch)	
Height	Standard: 705 mm (27,8 inch) Minimum possible: 690 mm (27,17 inch)	750 mm (29,53 inch)	
Curb weight	280 kg (617 lb)	325 kg (716 lb)	

Other positioning of electrical box	Stainless steel frame on feet	Forks for forklift and 45° fireplace	 Viniprepre Mobile
			
Truck sliding frame	Digital thermostat on control box	Double command with remote digital Thermostat	
			

Other available options on demands

///

Installation and commissioning are possible on request (the price will be according to the place)

